

Year	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100
1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	

Field of the Invention

15 Related Background Art

Among printing apparatuses each having a memory of a large capacity, there is also a printing apparatus such that received print data is successively and temporarily spooled in the memory of the large capacity, a printing order is controlled on the basis

of priorities and attributes of the print data, and a printing process is sequentially performed from a printer engine.

Further, in the recent printing apparatus, there
5 is considered a mail-box-function such that print data is accumulated in a non-volatile storing unit such as a hard disk or the like of the printing apparatus main body and the printing is instructed from an operation panel of the printing apparatus main body, thereby
10 performing the printing process for the first time.

The printer driver to form the print data, however, does not have the function to form the print data including the instruction such as to accumulate the print data into the printing apparatus main body as
15 mentioned above, so that a mode to accumulate the print data into the memory has to be set by the operation panel of the printing apparatus main body.

SUMMARY OF THE INVENTION

20 It is, therefore, the first object of the invention that in case of using a mail-box-function for a printing apparatus having the mail-box-function, a function to designate a mail box of the printing apparatus as a destination of print data is installed
25 for an information processing apparatus having a printer driver.

The mail-box-function considered in recent years

corresponds to one area that is common to the printing apparatus and a plurality of users accumulate print data into the same mail box (memory). Therefore, when the printing is instructed from the operation panel of the printing apparatus main body, which user's data exists in the mail box is known by the operator and there is a fear such that the print data is erroneously print processed.

It is, therefore, the second object of the invention that a plurality of mail box areas are provided for a printing apparatus and a function which can select any of a plurality of mail boxes of the printing apparatus to be designated as a destination is installed in an information processing apparatus having a printer driver.

When the user selects the print data by operating an operation panel of the printing apparatus main body, a list of data stored in the mail box is displayed. However, the contents to be displayed are a reading (receiving) time, a host name, and a file name based on an application which formed document data. That is, in the case where a Word document of a host name of "hayashi" has been accumulated in the mail box at 14:30 on January. 14, 1999, [19990114_1430 : hayashi : Word document] is displayed on the operation panel.

However, in the case where a plurality of files are accumulated in the mail box from the same person, it is

00440664 04300

difficult to recognize them as files formed by the same application and there is a fear such that they are erroneously print processed.

It is, therefore, the third object of the invention that a function which can designate a document name that is displayed on the operation panel of the printing apparatus main body is installed in an information processing apparatus having a printer driver.

To accomplish the above objects, therefore, according to the invention, there is provided an information processing apparatus for forming print data which can be interpreted by a printing apparatus in accordance with the document data formed by an application, comprising: setting means for setting either a mail box mode to accumulate the print data into the printing apparatus without printing it or a printer output mode to sequentially print the print data received by the printing apparatus; and forming means for forming the print data by adding information indicative of a destination in the printing apparatus in accordance with the output mode set by the setting means.

Other features and advantages of the present invention will be apparent from the following description taken in conjunction with the accompanying drawings, in which like reference characters designate

the same or similar parts throughout the figures thereof.

BRIEF DESCRIPTION OF THE DRAWINGS

5 Fig. 1 is a block diagram of a print system comprising a host computer and a printer;

 Fig. 2 shows software for printing in the host computer;

 Fig. 3 is a diagram of a memory map upon printing
10 in the host computer or printer setting;

 Fig. 4 is a flowchart for a procedure to set a data destination on a picture plane;

 Fig. 5 is a flowchart for a procedure to set a data destination on the picture plane;

15 Fig. 6 is a diagram showing a data destination setting picture plane;

 Fig. 7 is a diagram showing a device setting picture plane;

 Fig. 8 is a diagram showing a picture plane to
20 discriminate whether a mail box can be used or not;

 Fig. 9 is a diagram showing a picture plane to discriminate whether the mail box can be used or not;

 Fig. 10 is a diagram showing a data destination setting picture plane;

25 Fig. 11 is a diagram showing a data destination setting picture plane;

 Fig. 12 is a diagram showing a data destination

setting picture plane;

Fig. 13 is a diagram showing a message picture plane which is displayed in the case where a data destination is switched to a print-function;

5 Fig. 14 is a diagram showing a message picture plane which is displayed in the case where a data destination is switched to a mail-box-function; and

Fig. 15 is a diagram showing a mail box setting picture plane.

10

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

A print system comprising a printer having a function which can hold print data to a hard disk and a host computer using the printer will now be described
15 as an embodiment of the invention.

[Construction of print system]

Fig. 1 is a block diagram of a print system comprising a host computer 3000 and a printer 1500.

In Fig. 1, reference numeral 3000 denotes the host
20 computer according to the embodiment of an information processing apparatus of the invention. The host computer 3000 has a CPU 1 for executing a document process of a document in which a figure, an image, characters, a table (including a spreadsheet and the
25 like), and the like mixedly exist on the basis of a document processing program or the like stored in a program ROM of an ROM 3. The CPU 1 integratedly

An RAM 2 functions as a main memory, a work area, or the like of the CPU 1. A keyboard controller (KBC) 5 controls a key input from a keyboard 9 or a pointing device (not shown). A CRT controller (CRTC) 6 controls the display of a CRT display 10. A setting picture plane of the printer, which will be explained hereinlater, is also displayed on the CRT 10.

10 A disk controller (DKC) 7 controls an access to an
external memory 11 such as hard disk (HD), floppy disk
(FD), or the like to store a boot program, a printer
driver, various applications, font data, a user file,
an edit file, and the like. A printer controller
15 (PRTC) 8 is connected to the printer 1500 through a
predetermined bidirectional interface (bidirectional
I/F) 21 and executes a communication control process
with the printer 1500. The CPU 1 executes, for
example, a developing (rasterizing) process of an
20 outline font to a display information RAM set on the
RAM 2, thereby enabling WYSIWYG (What you see is what
you get: function for making the display contents
coincident with the print contents) on the CRT 10. The
CPU 1 also executes programs to realize procedures for
25 flowcharts, which will be explained hereinlater, opens
various registered windows on the basis of commands
instructed by a mouse cursor or the like (not shown) on

the CRT 10, and executes various data processes.

In the printer 1500, a CPU 12 integratedly controls accesses to various devices connected to a system bus 15 on the basis of control programs or the like stored in a program ROM of an ROM 13 and outputs
5 an image signal as output information to a printer engine 17 connected through an engine I/F 16.

Besides the mechanism to print, a staple stacker 171 is included in the printer engine 17. Although the
10 staple stacker 171 is provided separately from the printer, since it operates in association with the printer engine, it is regarded as a part of the printer engine 17.

The CPU 12 can communicate with the host computer
15 via the bidirectional I/F 21 and can notify the host computer 3000 of the information or the like in the printer. An RAM 19 functions as a main memory, a work area, or the like of the CPU 12. An input unit 18 controls a communication of status information or the
20 like such as printing state information or the like with the host computer 3000 through the bidirectional I/F 21 and can notify the host computer 3000 of the information or the like in the printer.

A memory controller (MC) 20 controls an access to
25 an external memory 14 such as hard disk (HD), floppy disk (FD), or the like to store a boot program, various applications, font data, a user file, an edit file, and

2025 RELEASE UNDER E.O. 14176

the like, and print data, which will be explained hereinlater. As for the external memory, a memory area is divided into a plurality of mail boxes, as will be explained hereinlater, and uses them.

5 An operation unit 1501 includes a display panel and a keyboard and allows information to be provided to the operator and allows a printing instruction or a selecting instruction to be inputted from the operator.

[Software construction of host computer]

10 In such a system, a construction on software for allowing the host computer 3000 to print is as shown in Fig. 2.

 An application 201, a graphic engine 202, a printer driver 203, and a system spooler 204 exist as
15 files stored in the external memory 11 and are program modules which are loaded in the RAM 2 and executed by an OS or a module using the module when they are executed.

 The application 201 and printer driver 203 can be
20 added to an FD as an external memory 11 or a CD-ROM (not shown) or can be added to an HD as an external memory 11 via a network (not shown). Although the application 201 stored in the external memory 11 is loaded in the RAM 2 and executed, when the printing is
25 performed from the application 201 to the printer 1500, the application 201 is similarly loaded in the RAM 2 and the outputting (drawing) is performed by using the

graphic engine 202 which can be executed. Although data that is outputted from the application to the graphic engine differs depending on the kind of OS, for example, in case of using Windows (registered trademark of Microsoft Corporation), a GDI function is outputted
5 as a drawing command to a GDI as a graphic engine.

The graphic engine 202 similarly loads the printer driver 203 prepared for every printing apparatus into the RAM 2 from the external memory 11, converts the GDI
10 (Graphic Device Interface) function as an output of the application 201 to a DDI (Device Driver Interface) function, and outputs it to the printer driver 203.

On the basis of the DDI function received from the GDI, the printer driver 203 converts it to a printer
15 control command comprising a PDL (Page Description Language) which can be interpreted by the printer 1500 and image data at a low level. The converted printer control command is outputted to the printer 1500 via the interface 21 through the system spooler 204 loaded
20 in the RAM 2 by the OS. In this instance, the printer driver transmits information to control the mail box to the printer 1500 together with the print data in accordance with a procedure, which will be explained hereinlater.

25 Fig. 3 shows an example of a memory map in the RAM 2 at the time of printing in the host computer 3000 or at the time of setting of the printer. An application

10

15

25

performing the printer setting when the printer setting

is called by the user. In the example, there are
setting items such as general, detail, page setting,
finish, paper feed, and the like every setting and the
user selects a desired picture plane in accordance with
5 the information to be set.

Fig. 6 shows the example in which a page setting
picture plane 601 is selected among the setting items.
The user sets each item on this picture plane and sets
a data destination by using the pointing device such as
10 a mouse or the keyboard.

Fig. 4 or 5 is a flowchart for a procedure to set
the data destination on the picture plane of Fig. 6.

First, in step S401, the CPU 1 executes a "Process
for discriminating whether the mail box can be used or
not". Fig. 5 is a flowchart for this process.
15

In step S501, whether the mail box can be used or
not is determined by pressing a "Get device
information" 701 or a check box 702 indicative of "Use
mail box" in Fig. 7.

20 When the "Get device information" button 701 is
pressed, a discrimination result about whether the mail
box can be used or not can be automatically obtained
from the printer. When the mail box can be used, the
box number and the box name of the mail box of the
25 printer are simultaneously obtained.

In the check box 702 of "Use mail box", the user
sets whether the mail box can be used or not by the

manual setting.

Fig. 8 shows a state where it is determined that the mail box cannot be used by obtaining the construction information or a state of the check box 702 in Fig. 7 in the case where the user sets a state where the mail box cannot be used by the manual setting.

Fig. 9 shows a state where it is determined that the mail box can be used by getting the construction information or a state of the check box 702 in Fig. 7 in the case where the user sets a state where the mail box can be used by the manual setting.

In next step S502, the CPU 1 discriminates whether the mail box can be used or not from the setting (state of 702 in Fig. 7) of the printer driver. When it is determined that the mail box can be used, in step S504, the icon of an output mode displayed at the upper right position in Fig. 6 is pressed, namely, a mail box button 1001 is set to "Enable" as shown in Fig. 10. The right side of the output mode icon indicates the mail box button 1001 and the left side shows a printer output button.

When it is decided in step S502 that the mail box cannot be used, in step S503, a mail box button 1201 is set to "Disable" as shown in Fig. 12. A display state of the mail box button 1201 is a gray display.

After completion of the process for discriminating

whether the mail box can be used or not in step S401 in Fig. 4, the processing routine advances to a control of the destination.

5 In step S402, the CPU 1 discriminates whether the mail box button has been selected as a destination setting of the printer driver or not.

When the mail box button 1101 is selected as shown in Fig. 11, in step S403, a message of Fig. 14 is displayed to thereby promote the user to set the
10 document name of the data to be transmitted and the box number and the user is allowed to set the document name and the box number on the user interface of the printer driver. The document name is a name for allowing the data stored in the mail box area of the printer main
15 body to be displayed on the operation panel and allowing the user to identify it. For example, it is preferable for the user to set a name by which the contents can be easily known like "Materials for Meeting A" or the like.

20 In step S405, the printer driver sets internal data indicative of the destination to the mail box. When the user wants to set the document name of the data to be transmitted to the mail box, in step S407, a mail box setting button 1102 in Fig. 11 is pressed, a
25 "Set mail box data" dialog box in Fig. 15 is opened and set on the user interface. Although not shown in Fig. 15, the box number and the box name of the mail box are

extracted from the device information obtained in step
S501 in Fig. 5 and the box name is set and displayed in
correspondence to the box number in Fig. 15. For
example, the box number and the box name are displayed
5 in the user interface of the printer driver on the host
computer in Fig. 15 in a manner such that the box No. 0
is set to "Common Box", the box No. 1 is set to "First
Party", the box No. 2 is set to "Second Party", the box
No. 3 is set to "hayashi", the box No. 4 is set to
10 "hosoi", the box No. 5 is set to "yamada", etc.

In step S408, the operator is allowed to designate
a document name column 1501 of data to be transmitted
and a mail box number column 1502 in Fig. 15, and the
designated document name and mail box number are set to
15 the printer driver.

The print data is stored on the basis of the
designated box number so as to correspond to the number
of mail box obtained by dividing the memory in the hard
disk of the printer main body. The designated document
20 name of the print data is registered in a management
table in the printer. The box number and the data
document name which are designated by the user in step
S408 are displayed on the operation panel 1501 of the
printer main body and can be confirmed.

25 When a printer output button is selected as shown
in Fig. 10 as a discrimination result in step S402, a
message of Fig. 13 is displayed in step S404 and the

After the mail box or printer is set as a destination, in step S409, print data comprising a PDL (Page Description Language) or image data at a low level is formed on the basis of a print quality or print style which has been set by the printer driver, and further, the internal data showing the destination. The printer driver adds information indicative of the destination (mail box number or direct output) in the printing apparatus, forms the print data, and transmits the formed print data to the printing apparatus.

The objects of the invention can be also accomplished by a method whereby a memory medium in which program codes of software to realize the functions of the embodiment mentioned above have been stored is fed to a system or an apparatus and a computer (or a CPU or an MPU) of the system or apparatus reads out and executes the program codes stored in the memory medium.

In this case, the program codes themselves read out from the memory medium realize the novel functions

of the invention and the memory medium in which the program codes have been stored constructs the invention.

As a memory medium to supply the program codes,
5 for example, it is possible to use a floppy disk, a hard disk, an optical disk, a magnetooptic disk, a CD-ROM, a CD-R, a magnetic tape, a non-volatile memory card, an ROM, or the like.

The invention also incorporates not only a case
10 where the computer executes the read-out program codes, so that the functions of the embodiment are realized, but also a case where an OS (Operating System) or the like which operates on the computer executes a part or all of the actual processes on the basis of
15 instructions of the program codes, and the functions of the embodiment mentioned above are realized by those processes.

Further, the invention also incorporates a case where the program codes read out from the memory medium
20 are written in a memory provided for a function expanding board inserted in the computer or a function expanding unit connected to the computer and, thereafter, a CPU or the like provided for the function expanding board or function expanding unit executes a
25 part or all of the actual processes on the basis of the instructions of the program codes, and the functions of the embodiment mentioned above are realized by the

processes.

The program codes themselves which are installed to the computer in order to realize the functions and processes of the invention by the computer also realize
5 the invention. That is, the computer programs themselves to realize the functions and processes of the invention are included in Claims of the invention.

As a method of supplying the computer program, the invention is not limited to the case where they are
10 stored in an FD or a CD-ROM and read out by the computer and installed therein as mentioned above. The computer is connected to a homepage of the Internet by using a browser of the client computer and the computer program itself of the invention or a compressed file
15 including an automatic installing function is downloaded from the homepage, so that the computer programs can be supplied. The invention can be also realized by a method whereby the program codes constructing the program of the invention are divided
20 into a plurality of files and each file is downloaded from a different homepage. That is, a WWW server for downloading the program file to realize the functions and processes of the invention by the computer to a plurality of users is also incorporated in Claims of
25 the invention.

The invention can be also realized by a method whereby the program of the invention is enciphered and

stored in a memory medium such as an FD or the like and distributed to the user, key information to decrypt is downloaded from the homepage through the Internet to the user who can clear predetermined conditions, and
5 the enciphered program is executed by using the key information and installed to the computer.

As described above, according to the invention, in case of using the mail-box-function for the printing apparatus having the mail-box-function, the function to
10 designate the mail box of the printing apparatus as destination of the print data is installed in the information processing apparatus having the printer driver. Therefore, the control mode can be switched to a mode of setting the destination to the mail box or
15 the mode to print the print data as it is without setting such a mode by the operation panel of the printing apparatus main body, and the user can easily handle the mail box.

In the information processing apparatus having the
20 printer driver, since which one of a plurality of mail boxes of the printing apparatus is designated as destination can be selected, the mail box divided per application can be efficiently used and the security to the print data in the mail box is improved.

25 In the information processing apparatus having the printer driver, since the document name to be displayed on the operation panel of the printing apparatus main

